

MORSØ - KS MINI

Routing Machine

Pneumatic/Electric

The perfect machine for producing the half-lap joint as found in Georgian window bars. It is used for both plant-on cassettes and rabbet bars.

MORSØ-KS MINI is operated with a pneumatic foot pedal which activates the router as well as the pneumatic clamping cylinders.

MORSØ-KS MINI routing machine is constructed for routing of grooves from 6-26mm (0.25-1") wide and up to 20mm/0.8" deep. Changing from one round nose router bit to another is quickly and easily done.

It is ideally used in conjunction with the MORSØ-N range of notch cutting machines.

MORSØ-KS MINI is CE approved.



MORSØ - KS MINI

Routing Machine

Pneumatic/Electric

TECHNICAL DATA

SUBJECT	SPECIFICATION
Leade	CCO (25")
Length	660 mm (25")
Width	460 mm (18")
Total machine height	1200 mm (47")
Height stand	760 mm (29")
Weight	49 kgs
Noise level	70 dBA
Air pressure	6-8 bar
Maximum height of workpiece	55 mm(2")
Maximum height of workpiece with 10 m	m cutter 50 mm (2")
Maximum groove depth	20 mm (¾")
Maximum groove diameter	Ø 20mm (¾")
Single phase	0,860 kW
Rpm	29000

MORSØ-KS MINI is delivered with:


- safety guard
- automatic forward movement of router
- automatic pneumatic clamping cylinders
- automatic centering of workpiece when clamped
- one size of router
- stand

ACCESSORIES:

additional size routers







MODELS

(all models can be equipped with Digital Control System)

MORSØ - KSD

MORSØ - KS MINI

MORSØ - KS

DISTRIBUTOR

